

SC 405



➔ Proximity T&A System with Access Control

Card Capacity : 30,000
Transaction Storage : 50,000
Card Reader : Yes
CPU : 32 bit High End Microprocessor
FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
Identification Speed : ≤ 0.1 sec
Display : Black & White
Keypad : 4 x 4 Keypads
LED Indicator : Green/Red
Schedule Bell/Speaker : Mini Speaker
Communication : TCP/IP,USB,RS485
Power Supply : 12V DC, 2amps / 3amps
Operating Temperature : 0°C to 45°C
Operating Humidity : 20% -80%
Dimension : 143 x 95.5 x39.5mm
Access Control : Wiegand : In & Out
Relay : Inbuilt relay to communicate with Locks,
Alarms & Door Sensors

Support Fire Alarm : Yes / Door Sensor ; Yes
Anti Passback : Yes / Door Bell : Yes
Support exit reader : KR 500E / Exit Button /
101 HE,50 time zones, 5 groups, 10 time combinations
Battery : No / Card Readers : Yes
Communication : No
Printer : No

Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

Compatible Software & SDK :

- Smart Office Suite Desktop
- etime tracklite Desktop & Web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications