

TF 1600



➔ Standalone Fingerprint Time Attendance & Access Control System

Fingerprint Templates : 3000
Card Storage : 30000
Transaction Storage : 1,00,000
Card Reader : Yes
CPU : 400MHz
Fingerprint Sensor : 500 DPI Optical Sensor
FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
Identification Speed : ≤ 0.5 sec
Algorithm Ver : 10
Display : NA
Keypad : NA
Schedule Bell/Speaker : Mini Speaker
Communication : RS485 , TCP/IP , USB-host
Push data : NO
Standard Features : DLST
Power Supply : DC 12V: 1.5Amp
Operating Temperature : -40°C - 45°C
Operating Humidity : 20% - 80%
Dimension : 62.5 x 185 x 41.5
Access Control : Wiegand : In & Out both

Relay : 12 V relay for lock
Bolt Lock or Strike lock
Support Fire Alarm : Yes / Door Sensor ; Yes
Anti Passback : Yes / Door Bell : Yes
Support exit reader : KR500,101 HE
Battery : No / Card Readers : Yes
Communication : No
Sensor : EM Lock (Standard)Mifare (Optional)

Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

Compatible Software & SDK :

- Smart office suite desktop
- Etime track lite desktop
- SDK for desktop applications
- Supports 3rd Party Payroll/HRMS/ERP and Other applications

Major Applications :

Time & Attendance , Canteen management,
School attendance, Production Management, Gym & clubs