



TF 1700

➔ Standalone Fingerprint Time Attendance & Access Control System - IP 65

Fingerprint Templates : 2200
Card Storage : 2200
Transaction Storage : Yes
Card Reader : Yes
CPU : 400MHz
Fingerprint Sensor : 500 DPI Optical sensor
(Optional Secugen STQC certified sensor)
FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
Identification Speed : ≤ 1 Sec
Algorithm Ver : 10
Display : 128 x 64 OIED with white Color
Keypad : 4 x 4 Keypad
Schedule Bell/Speaker : Mini Speaker
Communication : RS485 , TCP/IP , USB-host
Push data : NO
Standard Features : DLST
Power Supply : DC 12V: 1.5Amp
Operating Temperature : 0°C to 45°C
Operating Humidity : 20% -80%
Dimension : 90 x 190 x 3.5 mm
Access Control : Wiegand : In & Out
both 26 or 34 bit (With or without site code)

Relay : 12 V relay for lock EM lock,
Bolt Lock or Strike lock
Support Fire Alarm : Yes / Door Sensor ; Yes
Anti Passback : Yes / Door Bell : Yes
Support exit reader : KR500,101 HE
Battery : No / Card Readers : Yes
Communication : No
Sensor : Mifare

Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

Compatible Software & SDK :

- Smart office suite desktop and web
- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications