



**X 628 - C**

## ➔ Standalone TFT - Fingerprint Time & Attendance Terminal

Fingerprint Templates : 3000  
Card Capacity : 3000  
Transaction Storage : 1,00,000  
Card Reader : Yes  
CPU : 32 bit microprocessor 800 MHz  
Fingerprint Sensor : 500 DPI Optical Sensor  
FAR :  $\leq 0.0001\%$  / FRR :  $\leq 1\%$   
Identification Speed :  $\leq 0.5$  sec  
Algorithm Ver : 10  
Display : 2.8" Color TFT  
Keypad : 4 x 4 Keypad  
LED Indicator : Green/Red  
Schedule Bell/Speaker : Mini Speaker  
Communication : USB-host , TCP/IP  
Push data : Standard  
Standard features : Work Code,SMS,DLST,  
Self service query, Status Switch  
Power Supply : 5V DC, 2 A  
Operating Temperature : 0°C to 45°C  
Operating Humidity : 20% -80%  
Dimension : 190 x 135.8 x 51.5mm

Access Control : Wiegand : NO  
Relay : NO / Support Fire Alarm : NO  
Door Sensor ; NO /Anti Passback : NO  
Door Bell : NO  
Exit Readers Support exit readers NO  
Optional : Battery : NO  
Card Readers : NO / Communication : NO  
Printer : NO  
**Compatibility :**  
External Speaker output available (Optional)  
External Bulb output available (Optional)  
**Compatible Software & SDK :**  
- Smart office suite desktop and web  
- Etime track lite desktop & web  
- SDK for desktop applications  
- Web based Device Manager/  
ePush server using Push data.  
Helps developers & integrators  
- Supports 3rd Party Payroll/HRMS/ERP  
and Other applications